

Product Description Attic Stairs

Changes of technical details, due to continuous development, might happen without notice. Current status: www.wellhoefer.de

DIN EN
14975
(2007-03; Reg. Nr. 001)



■ Attic hatch

Casing dimensions (length/width) are 1.5 cm smaller than the ceiling opening.

■ Standard Sizes (dimensions of the ceiling opening in cm)

	StahlBlau	GutHolz	Liliput
Length	110, 120, 130, 140		90, 100
Width	60, 70		
Casing Height	25		

■ Custom-made (dimensions of the ceiling opening in cm)

	StahlBlau	GutHolz	Liliput
Length	105 - 160	100 - 160	70 - 160
Width	60 - 100	50 - 100	
Casing Height	17 - 90		
1 additional step	≥41	≥34	≥45
2 additional steps	≥74	≥67	≥78

Casing Height <25 cm: front notched

Length >140 or width >80: attic hatch door oversize

■ Frame

18 mm multifunction board, foil-coated, white, suited for load-bearing purposes in moist areas (EN 13986-P5)

■ Attic hatch door

16 mm chipboard, melanine resin-coated, white, circumferential ABS furniture edge

■ hoka twin-wall-sealing

TPV-profile with two degrees of hardening, lift range of sealing 4 mm, resistant against temperature / environmental influences and ageing, circumferential with groove in the attic hatch fold

■ Cover profiles

Plastic, white, special profile 40x6 mm, on mitre, pre-mounted adhesive tape, plug-in system with corner joints

■ Lifting mechanism

Well-engineered lever / spring system balances weight of stairs; even contact pressure for proper closing; ZD latch
Spring balancer dimensioned for long-time function, mechanical parts endurance tested

■ Swivel fitting

For controlling the attic hatch door; not visible when closed, allows cladding up to a thickness of 20 mm and a distributed load of 10 kg/m² (hatch door ≤1 m²) possible; request stronger springs for hatch door >1 m²

■ Low-Emission

Test Results: **HCHO** (formaldehyde) **1.5** µg/m³

TVOC (sum total of volatile organic compounds) **35** µg/m³
tested, DIN EN ISO 16000, TÜV Rheinland LGA Products

Clearly bellow the target values for harmlessness as specified by the Sentinel Haus Institut

Healthy housing!

■ Additional features (for all types of stairs)

Thermal protection WS3D as standard.

■ Thermal protection WS3D / WS4D

Material: **WS4D**: 96 mm polyethylene-thermodeck

WS3D: 48 mm polyethylene-thermodeck

Ceiling connection system for the installation gap:
double-sided adhesive sealing tape and insulation braid

Test Results: Attic stairs and connection system component tested:

WS4D: Insulation value U=0.58 W/(m²K)

tested, DIN EN ISO 12567-1: 2010-12, IBP Fraunhofer Stuttgart

WS3D: Insulation value U=0.80 W/(m²K)

tested, DIN EN ISO 12567-1: 2010-12, IBP Fraunhofer Stuttgart

Air-tightness Class 4 / sealing value a=0.01 m³/hm(daPa^{2/3})

tested, in accordance with DIN EN 12207 / DIN EN 1026: 2016-09, PFB

Climate-stability Class 3 climate category c/d

tested, based on DIN EN 12219: 2000-06, PFB Prüf. f. Bauelemente

incl. WS installation kit (contains all the required materials)

and the certified sealing system for **air-tight installation**

WS4D StahlBlau: Ceiling opening length min. 110 cm; ceiling height max. 311 cm.

WS4D GutHolz: Ceiling height max. 358 cm at ceiling opening length 150 cm.

WS4D Liliput: Ceiling opening length min. 77 cm.

**Insulated!
Air-tight!
Climate-stable!**

■ Thermal protection WSPH

Certified passive house component for cold climate.

All details on the Passive House Attic Stairs brochure.

**Passive House
Certificate!**

■ Guardrail

Solid wood; 4 posts: 33x33 mm; 2 triangular supports: 85x20 mm; 6 profiled strips: 47x20 mm; railing height 90 cm

Test: Stability 500N (DIN 1055)

incl. all required installation materials

**Building
regulations!**

■ Handrail

Wood: 18x38 mm; for StahlBlau/GutHolz

Telescope: 30 mm; only for Liliput concertina loft ladder

up to ceiling thickness ≤43 cm or ceiling opening length ≥100 cm

**User
safety!**

■ Lock

- Deadlock with round cylinder

- with profile cylinder: only for attic stairs with FS30 2S / FS90 2S

■ Flat roof exit

All details on the Flat Roof Exit brochure.

■ Maintenance

Lubricate joints / rotation points and control firm fit of screws annually. Pay attention to humidity at time of installation and when using. A User and Safety Guide is attached to all attic stairs.

Stairs and additional feature fire protection: Please turn over.

wellhoefer
TREPPEN AUS WÜRZBURG

All attic stairs including all required installation materials!

Product Description Attic Stairs

Changes of technical details, due to continuous development, might happen without notice. Current status: www.wellhoefer.de

■ Additional feature fire protection FS (for all types of stairs)

Component tested as installed system: Attic stairs and ceiling connection, installation gap up to a maximum of 20 mm width, combination with thermal protection. Installation in fire-protected ceiling openings in wooden beam ceilings, solid ceilings and suspended ceilings. Incl. FS installation kit (all required installation materials) and tested connection system for dry installation.

■ Fire protection FS30 Fire resistance 30 minutes from below (DIN 4102) EI,30 (ÖNORM B 3860)

Frame: 18 mm multifunction board with circumferential retardation strip, foil-coated, white, suited for load-bearing purposes in moist areas (EN 13986-P5)
Attic hatch door: 19 mm chipboard B1; 16 mm chipboard E1, melamine resin-coated, white, ABS furniture edge with retardation strips
Braid: Fire class B1, hardly flammable
Cover profiles: Plastic, white (see front)
Thermal protection WS3D as standard, WS4D/WSPH optionally

■ Fire protection FS30 2S Fire resistance 30 minutes from top and bottom (DIN 4102)

Frame: 2x 6,5 mm multiplex board with 6 mm silicate fire protection board in sandwich; externally 2x circumferential retardation strips; corner reinforcement with external aluminium brackets
Attic hatch door: 16 + 19 mm chipboards B1, melamine resin-coated, white, edges with retardation strips; 2x locking bolts
Braids: 2x; Fire class B1, hardly flammable
Cover profiles: Plastic, white (see front)
Thermal protection WS3D as standard

■ Fire protection FS90 2S Fire resistance 90 minutes from top and bottom (DIN 4102)

Frame: 2x 12 mm silicate fire protection boards with 18 mm multifunction board in sandwich; externally 2x circumferential retardation strips
Attic hatch door: 2x 16 mm chipboard B1, melamine resin-coated, white, with 25 mm calcium silicate board in sandwich, edges with retardation strips; 2x locking bolts
Braids: 2x; Fire class B1, hardly flammable
Cover strips top: Fire class A1
Cover profiles: Plastic, white (see front)
Thermal protection WS3D as standard

GutHolz/StahlBlau standard sizes: 120x60, 120/130/140x70, casing height 25 cm. Liliput always custom-made. Dimensions (min.-max.) of the ceiling opening in cm:

	FS30	StahlBlau	GutHolz	Liliput
Length	110 - 160	104 - 160	80 - 160	
Width	60 - 80		50 - 80	
Casing Height	17 - 90			
1 add. step	≥42	≥35	≥47	
2 add. steps	≥75	≥68	≥80	

Oversize: Length > 140

	FS30 2S	StahlBlau	GutHolz	Liliput
Length	110 - 140	104 - 140	80 - 140	
Width	60 - 80		50 - 80	
Casing Height	20 - 60			
1 add. step	≥42	≥35	≥47	

Casing height may not be greater than the ceiling thickness.


	FS90 2S	StahlBlau	GutHolz	Liliput
Length	110 - 140	105 - 140	85 - 140	
Width	65 - 70		55 - 70	
Casing Height	20 - 50			
1 add. step	≥44	≥38	≥50	

Casing height must correspond to the ceiling thickness!
From ceiling opening width < 65 cm: stairs 30 cm wide.
Ceiling to floor height: max. 360 cm (Liliput).

■ Stairs

■ GutHolz, 3-section folding wooden stairs

Stringers: Solid wood stringboard, thickness 20 x 85 mm
Steps: Corrugated, non-slip hardwood steps, depth 9 cm, thickness 17 mm, stair width standard 40 cm, Ceiling opening width < 60 cm: stairs 35 cm wide, Ceiling opening width < 55 cm: stairs 30 cm wide; dovetail joint
Ceiling height: from 197 to 360 cm ceiling to floor height; fine adjustment range per stair package +/- 5 cm; Ceiling to floor height determines minimum length of ceiling opening
Space requirement: Folding range F (147 - 217 cm) necessary; Swivel range not necessary



■ StahlBlau, 3-section folding steel stairs

Stringers: Steel tube stringer; \varnothing 27 mm
Steps: Welded steel steps, depth 11 cm, with profiled, embedded PVC step coating; stair width 40 cm
Stringers and steps powder-coated in blue
Ceiling height: from 237 to 314 cm ceiling to floor height; fine adjustment range per stair package +/- 5 cm; Ceiling to floor height determines minimum length of ceiling opening
Space requirement: Folding range F (153 - 194 cm) necessary; Swivel range not necessary

■ Liliput, concertina loft ladder

Stringers: Aluminium profile, thickness 10 x 34 mm
Steps: Profiled aluminium steps, depth 11 cm, thickness 26 mm, stair width standard 40 cm, Ceiling opening width < 60 cm: stairs 35 cm wide, Ceiling opening width < 55 cm: stairs 30 cm wide
Ceiling height: from 190 to 360 cm ceiling to floor height; Ceiling to floor height determines minimum length of ceiling opening
Space requirement: 90 - 145 cm necessary depending on ceiling to floor height; also suited for small ceiling openings

The specific space requirement (= folding range of the 3-section attic stairs and/or touchdown point with concertina loft ladders) depends on the ceiling to floor height. We recommend to add a further 50 cm of space for a more comfortable use of the stairs.

All attic stairs are manufactured in accordance with DIN and withstand mechanical stress of a maximum of 150 kg.

wellhöfer
TREPPEN AUS WÜRZBURG